

FIRST REGULAR SESSION

# HOUSE BILL NO. 939

## 94TH GENERAL ASSEMBLY

---

INTRODUCED BY REPRESENTATIVE DAVIS.

Read 1st time February 21, 2007 and copies ordered printed.

D. ADAM CRUMBLISS, Chief Clerk

2272L.01I

---

### AN ACT

To amend chapter 307, RSMo, by adding thereto one new section relating to motorcycle headlight modulators.

---

*Be it enacted by the General Assembly of the state of Missouri, as follows:*

Section A. Chapter 307, RSMo, is amended by adding thereto one new section, to be known as section 307.128, to read as follows:

**307.128. 1. A headlamp on a motorcycle may be wired to modulate either the upper beam or the lower beam from its maximum intensity to a lesser intensity provided that:**

**(1) The rate of modulation shall be two hundred forty plus or minus forty cycles per minute;**

**(2) The headlamp shall be operated at a maximum power for fifty to seventy percent of each cycle;**

**(3) The lowest intensity at any test point shall not be less than seventeen percent of the maximum intensity measured at the same point;**

**(4) The modulator switch shall be wired in the power lead of the beam filament being modulated and not in the ground side of the circuit;**

**(5) Means shall be provided so that both the lower beam and the upper beam remain operable in the event of a modulation failure;**

**(6) The system shall include a sensor mounted with the axis of its sensing element perpendicular to a horizontal plane. Headlamp modulation shall cease whenever the level of light emitted by a tungsten filament operating at three thousand degrees kelvin is either**

EXPLANATION — Matter enclosed in bold-faced brackets [thus] in the above bill is not enacted and is intended to be omitted from the law. Matter in **bold-face** type in the above bill is proposed language.

16 less than two hundred seventy lux of direct light for upward pointing sensors or less than  
17 sixty lux of reflected light for downward pointing sensors. The light is measured by a  
18 silicon cell type light meter that is located at the sensor and pointing in the same direction  
19 as the sensor. A Kodak Gray Card is placed at ground level to simulate the road surface  
20 in testing downward pointing sensors;

21 (7) Means shall be provided so that both the lower and upper beam function at  
22 design voltage when the headlamp control switch is in either the lower or upper beam  
23 position when the modulator is off.

24 2. Each motorcycle headlamp modulator not intended as original equipment, or its  
25 container, shall be labeled with the maximum wattage, and the minimum wattage  
26 appropriate for its use. Additionally, each such modulator shall comply with the  
27 provisions of paragraphs (1) to (7) of subsection 1 of this section when connected to a  
28 headlamp of the maximum rated power and headlamp of the minimum rated power, and  
29 shall provide means so that the modulated beam functions at design voltage when the  
30 modulator is off. Instructions, with a diagram, shall be provided for mounting the light  
31 sensor including location on the motorcycle, distance above the road surface, and  
32 orientation with respect to the light.

✓